

FSP-SS-S4

Floor Scale, Stainless Steel



Features:

- 17-4PH & 304 Stainless steel heavy-duty industrial design
- Rigid steel channel frame
- Pre-trimmed corners
- Threaded eyebolt holes for easy lifting

Complete Set Includes:

- IP68/IP69K stainless steel load cells 563YS, OIML MAA & NETP certified
- 4 swivel stainless steel feet AMFS4 with removable rubber base
- 2 eyebolts
- 1 IP65 stainless steel junction box J04ES-FS
- 1 level bubble

DIMENSIONS

PART NUMBER	RATED CAPACITY	LOAD CELL CAPACITY	SIZE IN INCHES (W x L x H)	WEIGHT	DECK PLATE THICKNESS
FSP3x3-500kg-SS-S4	500kg	563YS-300kg	36" x 36" x 4"	75kg / 165 lb	0.16" / 4mm
FSP3x3-1t-SS-S4	1t	563YS-500kg	36" x 36" x 4"	75kg / 165 lb	0.16" / 4mm
FSP3x3-2.5t-SS-S4	2.5t	563YS-1t	36" x 36" x 4"	75kg / 165 lb	0.16" / 4mm
FSP3x3-1Klb-SS-S4	1Klb	563YS-500lb	36" x 36" x 4"	75kg / 165 lb	0.16" / 4mm
FSP3x3-2Klb-SS-S4	2Klb	563YS-1Klb	36" x 36" x 4"	75kg / 165 lb	0.16" / 4mm
FSP3x3-5Klb-SS-S4	5Klb	563YS-2.5Klb	36" x 36" x 4"	75kg / 165 lb	0.16" / 4mm
FSP4x4-500kg-SS-S4	500kg	563YS-300kg	48" x 48" x 4"	120kg / 265 lb	0.20" / 5mm
FSP4x4-1t-SS-S4	1t	563YS-500kg	48" x 48" x 4"	120kg / 265 lb	0.20" / 5mm
FSP4x4-2.5t-SS-S4	2.5t	563YS-1t	48" x 48" x 4"	120kg / 265 lb	0.20" / 5mm
FSP4x4-5t-SS-S4	5t	563YS-2t	48" x 48" x 4"	120kg / 265 lb	0.20" / 5mm
FSP4x4-1Klb-SS-S4	1Klb	563YS-500lb	48" x 48" x 4"	120kg / 265 lb	0.20" / 5mm
FSP4x4-2Klb-SS-S4	2Klb	563YS-1Klb	48" x 48" x 4"	120kg / 265 lb	0.20" / 5mm
FSP4x4-5Klb-SS-S4	5Klb	563YS-2.5Klb	48" x 48" x 4"	120kg / 265 lb	0.20" / 5mm
FSP4x4-10Klb-SS-S4	10Klb	563YS-4Klb	48" x 48" x 4"	120kg / 265 lb	0.20" / 5mm
FSP5x5-2.5t-SS-S4	2.5t	563YS-1t	59" x 59" x 4"	200kg / 441 lb	0.24" / 6mm
FSP5x5-5t-SS-S4	5t	563YS-2t	59" x 59" x 4"	200kg / 441 lb	0.24" / 6mm
FSP5x5-5Klb-SS-S4	5Klb	563YS-2.5Klb	59" x 59" x 4"	200kg / 441 lb	0.24" / 6mm
FSP5x5-10Klb-SS-S4	10Klb	563YS-SE5Klb	59" x 59" x 4"	200kg / 441 lb	0.24" / 6mm
FSP4x6-2.5t-SS-S4	2.5t	563YS-1t	48" x 72" x 4"	180kg / 397 lb	0.20" / 5mm
FSP4x6-5t-SS-S4	5t	563YS-2t	48" x 72" x 4"	180kg / 397 lb	0.20" / 5mm
FSP4x6-5Klb-SS-S4	5Klb	563YS-2.5Klb	48" x 72" x 4"	180kg / 397 lb	0.20" / 5mm
FSP4x6-10Klb-SS-S4	10Klb	563YS-SE5Klb	48" x 72" x 4"	180kg / 397 lb	0.20" / 5mm
FSP5x7-2.5t-SS-S4	2.5t	563YS-1t	59" x 84" x 4"	260kg / 573 lb	0.24" / 6mm
FSP5x7-5t-SS-S4	5t	563YS-2t	59" x 84" x 4"	260kg / 573 lb	0.24" / 6mm
FSP5x7-5Klb-SS-S4	5Klb	563YS-2.5Klb	59" x 84" x 4"	260kg / 573 lb	0.24" / 6mm
FSP5x7-10Klb-SS-S4	10Klb	563YS-SE5Klb	59" x 84" x 4"	260kg / 573 lb	0.24" / 6mm

OPTIONAL ACCESSORIES

- Indicators (page 148/149)
- Ramps-17 (page 167)
- Bumper Guards (page 172)



Measurement Canada Approval for
- 3X3-5Klb - 4X4-5Klb - 5X5-5Klb



NTEP 1:5 000 Class III Approval for
- 3X3-1Klb - 4X4-1Klb - 5X5-1Klb
- 3X3-2Klb - 4X4-2Klb - 5X5-2Klb
- 3X3-5Klb - 4X4-5Klb - 5X5-5Klb
- 3X3-10Klb - 4X4-10Klb - 5X5-10Klb