



J04ES; J04SS

Stainless Steel



- Features:
- Enclosure Material: Stainless steel SS304
 - Number of cells: 2 - 4 single cells
 - Trimming: Individual cell with excitation or signal trim
 - Equipped with independent potentiometers
 - Captive stainless steel screws
 - IP Rating: IP65



DIMENSIONS

	C	H	L	L1	W	W1
mm	8	44	144	112	142	128
inches	0.3	1.7	5.7	4.4	5.6	5.0

SPECIFICATIONS

Number of Cells	2 - 4 single cells	Trimming	Individual cell with excitation or signal trim
Input Cable Fittings	M16: 4mm - 8mm diameter cable	Enclosure Material	Stainless steel SS304
Output Cable Fittings	M20: 5mm - 9mm diameter cable	IP Rating	IP65

TRIMMING RANGE

Load Cell Resistance	Signal Trim	Excitation Trim
350 Ω	3.6% of output	2.3% of output
700 Ω	6.3% of output	1.3% of output
1000 Ω	7.0% of output	1.0% of output

PART NUMBER

Trimming	Lightning Protection	Part No.	Weight (kg) Approx.
Excitation	No	J04ES	0.7
Signal	No	J04SS	0.7
Excitation	Yes	J04ES-II	0.7
Signal	Yes	J04SS-II	0.7

MOTHERBOARD LAYOUT

