

OCSD Series

OCSD Indicator P180



FEATURES

- **Palm Size:** small size enclosure of only 28X70X90mm which is easy for carrying around
- **Wireless two way communication:** can do tare, zero scale, calibration and parameter setting
- **Display:** five 12mm high LCD digits with backlight which can show the status of battery power, tare, zero, peak and stable
- **USB Port:** equipped with USB port for easy connection and communication with PC
- **Power Supply:** power supply through USB connection or Lithium battery (included)
- **Operating Temperature:** -20°C to 60°C
- **Antenna:** concealed antenna as an integral part of the receiver
- **Updating Rate:** 12 times per second from load cell
- **Radio Frequency:** 2.4GHz wireless transmission of up to 30m distance and 128 available channels. 433MHz or 868MHz transmission frequency is available upon request

OCSD Indicator P380



FEATURES

- **Hand Held Size:** the enclosure is 220X105X50 and is designed for portable handheld operation
- **Wireless two way communication:** can do tare, zero scale, calibration and parameter setting
- **Display:** five 25mm high LCD digits with backlight which can show the status of battery power, tare, zero, peak and stable
- **Battery:** four AA size alkaline batteries can allow 50 hours continuous operation
- **Set Points:** Two user programmable Set-Points can be used for safety and warning applications, or for weighing limit
- **Communication:** RS232 communication port is available for easy extract of data or printing operation, continuous output can drive a scoreboard
- **Operating Temperature:** -20°C to 60°C
- **Antenna:** concealed antenna as an integral part of the receiver
- **Updating Rate:** 12 times per second from load cell
- **Radio Frequency:** 2.4GHz wireless transmission of up to 30 m distance and 128 available channels. 433MHz or 868MHz transmission frequency is available upon request