



RATED CAPACITY	DIMENSIONS										
	H	L	L1	L2	L3	L4	W	W1	W2	T	
108JA:											
kg/mm											
20-100	25.0	150.0	32.5	6.0	19.0	100.0	45.0	7.5	30.0	M8 Depth15	
LE60-LE100; SE150-SE400	40.0	150.0	32.5	6.0	19.0	100.0	45.0	7.5	30.0	M8 Depth20	
150-400; SE600	40.0	150.0	38.5	6.0	25.0	88.0	75.0	12.5	50.0	M8 Depth20	
500-2,000	50.0	200.0	52.0	14.0	25.0	122.0	100.0	15.0	70.0	M10 Depth23	
lb/inches (conversion of above dimensions)											
44.1-220.5	0.98	5.91	1.28	0.24	0.75	3.94	1.77	0.30	1.18	M8 Depth0.59	
LE132.3-LE220.5; SE330.7-SE881.8	1.57	5.91	1.28	0.24	0.75	3.94	1.77	0.30	1.18	M8 Depth0.79	
330.7-881.8; SE1,322.8	1.57	5.91	1.52	0.24	0.98	3.46	2.95	0.49	1.97	M8 Depth0.79	
1,102.3-4,409.2	1.97	7.87	2.05	0.55	0.98	4.80	3.94	0.59	2.76	M10 Depth0.91	
108JA-21:											
kg/mm											
30-150	38.0	150.0	44.0	6.3	25.4	86.6	38.0	-	25.4	M6 Depth 15	
lb/inches (conversion of above dimensions)											
66.14-330.70	1.50	5.91	1.73	0.25	1.00	3.41	1.50	-	1.00	M6 Depth 0.59	

SPECIFICATIONS			
Full Scale Output	2.0 mV/V ± 10%	Reference Max. Platform Size	108JA: Capacity: 20-100kg: 460×600 mm Capacity: 150-400kg: 600×600 mm Capacity: 500kg-2t: 900×900 mm 108JA-21: 500×500 mm
Zero Balance	±0.02 mV/V		
Non-linearity	< ±0.017%		
Repeatability	< ±0.017%		
Hysteresis Error	< ±0.017%	Nominal Temperature Range	-10°C to 40°C / 14°F to 104°F
Creep in 30 min.	< ±0.017%	Seal Type / IP Rating	Environmentally Sealed / IP66
Input Resistance	415Ω ± 15	Cable Color Code	108JA: Exc+ Red Exc- Black Sig+ Green Sig- White Shield Bare 108JA-21: Exc+ Green Exc- Black Sig+ Red Sig- White Shield Bare
Output Resistance	350Ω ± 3		
Element Material	Aluminum, Clear Anodized		
Recommended Excitation	10V (15V Maximum)		
Safe Overload	150% of full scale		
Breaking Overload	300% of full scale		
Insulation Resistance	>2 [50V DC] GΩ		

PART NUMBER*		
Rated Capacity	Part No.	Weight Approx. (kg)
20kg	108JA-20kg	0.4
50kg	108JA-50kg	0.5
60kg	108JA-60kg	0.5
LE60kg	108JA-LE60kg	0.7
75kg	108JA-75kg	0.5
LE75kg	108JA-LE75kg	0.7
100kg	108JA-100kg	0.5
LE100kg	108JA-LE100kg	0.7
SE150kg	108JA-SE150kg	0.7
150kg	108JA-150kg	1.1
SE200kg	108JA-SE200kg	0.7
200kg	108JA-200kg	1.1
SE300kg	108JA-SE300kg	0.7
300kg	108JA-300kg	1.1
SE400kg	108JA-SE400kg	0.7
400kg	108JA-400kg	1.1
500kg	108JA-500kg	2.5
SE600kg	108JA-SE600kg	1.1
750kg	108JA-750kg	2.5
1t	108JA-1t	2.5
1.5t	108JA-1.5t	2.5
2t	108JA-2t	2.6

PART NUMBER		
Rated Capacity	Part No.	Weight (kg) Approx.
30kg	108JA-30kg-21	0.6
50kg	108JA-50kg-21	0.6
75kg	108JA-75kg-21	0.6
100kg	108JA-100kg-21	0.6
150kg	108JA-150kg-21	0.6

INTERCHANGEABLE REFERENCE	
Brand	Model
108JA-21	
Vishay-Tedea Huntleigh	1242
Mettler Toledo	MT1241

20kg-500kg: NTEP 1:5 000 Class III, Single Cell;
 SE600kg-2t: NTEP 1:4 000 Class III, Single Cell
 20kg-30kg: OIML MAA C7.5, Y=20 000;
 50kg-500kg: OIML MAA C6, Y=29 000;
 SE600kg-2t: OIML MAA C4, Y=4 000
 For further available P/N's & specifications per NTEP/OIML classes, please contact us.

* ATEX, FM, IECEx approved versions carry the "-Ex" suffix.

All product specifications, statements, information and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all conditions. It is the customer's responsibility to validate that a particular product with the properties described in the product specifications is suitable for use in their applications. Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge of product information at the time a publication was made, but are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another manufacturer.

Any use of product outside of specifications or any storage or installation inconsistent with product guidance voids and warranty.

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by ANYLOAD with reference to the use of ANYLOAD's products produces no obligation or liability for the advice given or results obtained.

Although ANYLOAD designs and manufactures its products to the most stringent quality and safety standards, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services or deliverables for use in high risk applications including medical life support, medical device, direct physical patient contact, water treatment, nuclear facilities, weapon systems, mass and air transportation control, flammable environments, or any other potentially life critical uses. Customer understands and agrees that ANYLOAD makes no assurances that the products, services or deliverables are suitable for any high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process. Although all product - related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required. Please contact authorized ANYLOAD personnel to obtain special terms and conditions regarding products designed for such applications or otherwise satisfy specific safety requirements.