



RATED CAPACITY	H	L	L1	L2	L3	L4	W	W1	W2	T
<b>108JA:</b>										
<b>kg/mm</b>										
20-100	25.0	150.0	32.5	6.0	19.0	100.0	45.0	7.5	30.0	M8 Depth15
LE60-LE100; SE150-SE400	40.0	150.0	32.5	6.0	19.0	100.0	45.0	7.5	30.0	M8 Depth20
150-400; SE600	40.0	150.0	38.5	6.0	25.0	88.0	75.0	12.5	50.0	M8 Depth20
500-2,000	50.0	200.0	52.0	14.0	25.0	122.0	100.0	15.0	70.0	M10 Depth23
<b>lb/inches (conversion of above dimensions)</b>										
44.1-220.5	0.98	5.91	1.28	0.24	0.75	3.94	1.77	0.30	1.18	M8 Depth0.59
LE132.3-LE220.5; SE330.7-SE881.8	1.57	5.91	1.28	0.24	0.75	3.94	1.77	0.30	1.18	M8 Depth0.79
330.7-881.8; SE1,322.8	1.57	5.91	1.52	0.24	0.98	3.46	2.95	0.49	1.97	M8 Depth0.79
1,102.3-4,409.2	1.97	7.87	2.05	0.55	0.98	4.80	3.94	0.59	2.76	M10 Depth0.91
<b>108JA-21:</b>										
<b>kg/mm</b>										
30-250	38.0	150.0	44.0	6.3	25.4	86.6	38.0	-	25.4	M6 Depth 15
<b>lb/inches (conversion of above dimensions)</b>										
66.14-551.16	1.50	5.91	1.73	0.25	1.00	3.41	1.50	-	1.00	M6 Depth 0.59

SPECIFICATIONS			
Full Scale Output	2.0 mV/V ± 10%	Reference Max. Platform Size	108JA: Capacity: 20-100kg: 460×600 mm
Zero Balance	± 0.02 mV/V		Capacity: 150-400kg: 600×600 mm
Non-linearity	< ± 0.017%		Capacity: 500kg-2t: 900×900 mm
Repeatability	< ± 0.017%		108JA-21: 500×500 mm
Hysteresis Error	< ± 0.017%	Nominal Temperature Range	-10°C to 40°C / 14°F to 104°F
Creep in 30 min.	< ± 0.017%	Seal Type / IP Rating	Environmentally Sealed / IP66
Input Resistance	415Ω ± 15	Cable Color Code	108JA:
Output Resistance	350Ω ± 3		Exc+ Red      Exc- Black
Element Material	Aluminum, Clear Anodized		Sig+ Green      Sig- White      Shield Bare
Recommended Excitation	10V (15V Maximum)		108JA-21:
Safe Overload	150% of full scale		Exc+ Green      Exc- Black
Breaking Overload	300% of full scale		Sig+ Red      Sig- White      Shield Bare
Insulation Resistance	>2 [ 50V DC ] GΩ		

PART NUMBER*		
Rated Capacity	Part No.	Weight Approx. (kg)
20kg	108JA-20kg	0.4
50kg	108JA-50kg	0.5
60kg	108JA-60kg	0.5
LE60kg	108JA-LE60kg	0.7
75kg	108JA-75kg	0.5
LE75kg	108JA-LE75kg	0.7
100kg	108JA-100kg	0.5
LE100kg	108JA-LE100kg	0.7
SE150kg	108JA-SE150kg	0.7
150kg	108JA-150kg	1.1
SE200kg	108JA-SE200kg	0.7
200kg	108JA-200kg	1.1
SE300kg	108JA-SE300kg	0.7
300kg	108JA-300kg	1.1
SE400kg	108JA-SE400kg	0.7
400kg	108JA-400kg	1.1
500kg	108JA-500kg	2.5
SE600kg	108JA-SE600kg	1.1
750kg	108JA-750kg	2.5
1t	108JA-1t	2.5
1.5t	108JA-1.5t	2.5
2t	108JA-2t	2.6

PART NUMBER		
Rated Capacity	Part No.	Weight (kg) Approx.
30kg	108JA-30kg-21	0.6
50kg	108JA-50kg-21	0.6
75kg	108JA-75kg-21	0.6
100kg	108JA-100kg-21	0.6
150kg	108JA-150kg-21	0.6
250kg	108JA-250kg-21	0.6

INTERCHANGEABLE REFERENCE	
Brand	Model
108JA-21	
Anyload	108LAMT
Vishay-Tedea Huntleigh	1242
Vishay-Tedea Huntleigh	1241(metric thread)
Mettler Toledo	MT1241

20kg-500kg: NTEP 1:5 000 Class III, Single Cell; SE600kg-2t: NTEP 1:4 000 Class III, Single Cell  
 20kg-30kg: OIML MAA C7.5, Y=20 000;  
 50kg-500kg: OIML MAA C6, Y=29 000;  
 SE600kg-2t: OIML MAA C4, Y=4 000  
 For further available P/N's & specifications per NTEP/OIML classes, please contact us.

\* ATEX, FM, IECEx approved versions carry the "-Ex" suffix.