



### DIMENSIONS

RATED CAPACITY	C1	C2	H	H1	L	L1	L2	L3	L4	W	T
250-4,000; SE5,000	0.53	0.53	1.25	0.62	5.12	2.25	3.00	1.00	0.62	1.25	1/2-20 UNF-2B
5,000-10,000	0.78	0.78	1.50	0.75	6.75	3.00	3.75	1.50	0.75	1.50	3/4-16 UNF-2B
15,000-20,000	1.03	1.03	2.00	1.00	8.88	4.00	4.88	2.00	1.00	2.00	1-14 UNS-2B

### SPECIFICATIONS

<b>Full Scale Output</b>	3.0 mV/V ± 0.25%	<b>Element Material</b>	Alloy Steel, Nickel Plated
<b>Zero Balance</b>	± 0.02 mV/V	<b>Recommended Excitation</b>	10V (15V Maximum)
<b>Non-linearity</b>	Cap. ≤ 750lb: < ± 0.03%;	<b>Insulation Resistance</b>	> 2 [ 50V DC ] GΩ
	Cap. > 750lb: < ± 0.02%	<b>Compensated Temperature Range</b>	-10°C to 50°C / 14°F to 122°F
<b>Repeatability</b>	< ± 0.02%	<b>Safe Overload</b>	150% of full scale
<b>Hysteresis Error</b>	Cap. ≤ 750lb: < ± 0.03%;	<b>Breaking Overload</b>	300% of full scale
	Cap. > 750lb: < ± 0.02%	<b>Seal Type / IP Rating</b>	Environmentally Sealed / IP67
<b>Creep in 30 min.</b>	< ± 0.025%	<b>Cable Color Code</b>	Exc+ Red      Exc- Black Sig+ Green    Sig- White Shield Bare
<b>Input Resistance</b>	350Ω ± 7		
<b>Output Resistance</b>	350Ω ± 3		

### PART NUMBER\*

Rated Capacity	Part No.	Weight (kg) Approx.
250lb	563YH-23A-250lb	1.0
500lb	563YH-23A-500lb	1.0
750lb	563YH-23-750lb	1.0
1Klb	563YH-23-1Klb	1.0
1.5Klb	563YH-23-1.5Klb	1.0
2Klb	563YH-23-2Klb	1.0
2.5Klb	563YH-23-2.5Klb	1.0
4Klb	563YH-23-4Klb	1.0
SE5Klb	563YH-23-SE5Klb	1.0
5Klb	563YH-23-5Klb	1.8
10Klb	563YH-23-10Klb	1.8
15Klb	563YH-23-15Klb	4.0
20Klb	563YH-23-20Klb	4.0

SE refers to small envelope

\* ATEX, FM, IECEx approved versions carry the "-Ex" suffix.

250lb-2.5Klb: NTEP 1:5 000 Class III, Single Cell;  
NTEP 1:9 500 Class III, Multiple Cell  
4Klb-20Klb: NTEP 1:6 000 Class III, Single Cell;  
NTEP 1:10 000 Class III, Multiple Cell

1Klb-5Klb: OIML MAA C4, Y=15 000;  
10Klb-20Klb: OIML MAA C6, Y=8 500

For further available P/N's & specifications per NTEP/OIML classes, please contact us.

[www.anyload.com](http://www.anyload.com)

© 2023 ANYLOAD V2 dimensions and specifications subject to change without notice

### INTERCHANGEABLE REFERENCE

Brand	Model
Coti Global	CG-23
Rice Lake	RL30000
Rice Lake	RL35023
Vishay Celtron	SQB
Vishay Revere Transducers	.5123
Vishay Sensortronics	.65023A
Vishay TedeA-Huntleigh	.3411