

808 Series

Remote Display Series



Specifications

Enclosure Material: Powder Coated Mild Steel (IP65)

Display: 6-digit, 7-segment, 125mm(5*) LEDs

Visibility: Max 75m(250ft) @1500mcd, 120° angle

Power Supply: 100-240VAC, 1.2A, 50/60Hz, UL approved

Communication: Independent RS232, RS422/485, 20mA

300,600,...,9600,...,38400, 57600 Baud

Dimensions: 565mm X 250mm X 89mm
22.2" X 9.8" X 3.5"

Operating Temp: -40°C to 50°C (-40°F to 120°F)

Box Ventilation: Breather vent to avoid condensation.

Input & Output: 2 dry contact switches and 1 form C relay

Features

- Weather proof steel + GORE breather vent
- Automatically set communication baud rates
- Automatically detect indicator string protocols
- Independent RS232, RS422, RS485, 20mA current loop.
- Echo out and addressable multi display configuration.
- Switch inputs and relay output to control traffic lights.





Description

The ANYLOAD 808-series are the newest generation industrial remote displays designed to be versatile, rugged, durable, and easy to install. They are incorporated with Auto-Learn communicate and protocol feature for compatibility with wide range of indicators and weighing instruments. The WL900 Wireless RF Transceiver is an add-on wireless device exclusively to connect to the 808 Series and sold separately.

Diagram - 808 Series

