

Cable Armor & End Fitting



Features:

- Flexible protective armor, galvanized steel inside, PVC outside
- Protects cable from rodents and mechanical damage
- 0.63" (16mm) internal diameter, 0.8" (20mm) external diameter
- 2" (50mm) minimum bending radius
- 100m per roll
- Cable armor and fitting sold separately

PART NUMBER		
Description	Part No.	Weight (kg) Approx.
Cable Armor (end fitting not included), 100m per roll.....	CAHP20-1/2-100m.....	18.0
End fitting only.....	CAEFGI-1/2.....	0.1

CB

Load Cell Cable



CABLE, CONNECTOR & ACCESSORIES

SPECIFICATIONS					
Model	CB4			CB6	
Number of Wires	4			6	
Outside Diameter	5.1mm ± 0.2	7.6mm ± 0.3	8mm ± 0.3 (RP)	7.6mm ± 0.3	8mm ± 0.3 (RP)
Cross Section Area of Each Wire	0.283mm ²	0.478mm ²	0.478mm ²	0.478mm ²	0.478mm ²
Temperature	-30°C to 85°C / -22°F to 185°F				
Wire Resistance	≤ 0.09Ω/m				
Screen	1				
Capacity	≤ 80PF/m				
Length	100m (loose) / 300m (with reel)				
Jacket Material	PVC or Rodent Protection				
Jacket Colour	Black or Silver				

PART NUMBER				
Description	With Reel	Diameter	Part No.	Weight (kg) Approx.
PVC cable with 4 wire	No	φ 5.1	CB4-5.1-100m.....	3.2
PVC cable with 4 wire	Yes.....	φ 5.1	CB4-5.1-300m.....	10.3
PVC cable with 4 wire	No	φ 7.6	CB4-7.6-100m.....	7.9
PVC cable with 4 wire	Yes.....	φ 7.6	CB4-7.6-300m.....	23.7
PVC cable with 6 wire	No	φ 7.6	CB6-7.6-100m.....	7.4
PVC cable with 6 wire	Yes.....	φ 7.6	CB6-7.6-300m.....	22.8
PVC cable with 12 wire	Yes.....	φ 7.6	CB12-7.6-300m.....	27.0
Rodent protection cable with 4 wire.....	No.....	φ 8.0.....	CB4RP-8-100m.....	11.9
Rodent protection cable with 4 wire.....	Yes.....	φ 8.0.....	CB4RP-8-300m.....	-
Rodent protection cable with 6 wire.....	No.....	φ 8.0.....	CB6RP-8-100m.....	10.5
Rodent protection cable with 6 wire.....	Yes.....	φ 8.0.....	CB6RP-8-300m.....	38.2