

FSP Series

FEATURES

- Mild steel construction
- 5mm thick deck plate with checkered safety tread
- Steel grid channel frame
- Painted mild steel
- Pre-corner error adjustment
- Threaded eyebolt holes for easy lifting (eyebolts included)
- Installed with:
 - *4 high accuracy IP67 alloy steel shear beam load cells (563YH) (OIML MAA C6, Y=8,500 and NTEP 1:5000 Class III, Multiple Cell)
 - *4 swivel mild steel feet with removable rubber base (AMF-F-1/2)
 - *1 IP67 aluminum 4-way junction box (J04EA-16)
 - *2 eyebolts
 - *Level bubble



*NTEP Approval for
 1Klb: FSP-3X3
 5Klb: FSP-3X3
 FSP-4X4
 FSP-5X5
 10Klb: FSP-3X3
 FSP-4X4
 FSP-5X5



*Measurement Canada Approval for
 5Klb: FSP-3X3
 FSP-4X4
 FSP-5X5
 10Klb(Pending): FSP-3X3
 FSP-4X4
 FSP-5X5

Part#	FSP5X5-5Klb	FSP5X5-10Klb
Capacity	5000lb	10000lb
Division	1lb	2lb
Platform Size	59in X 59in/ 150cm X 150cm	59in X 59in/ 150cm X 150cm
Platform Material	Mild Steel	Mild Steel
Net Weight	441lb / 200kg	441lb / 200kg
Operating Temp.	0 - 40°C / 32 - 104°F	0 - 40°C / 32 - 104°F

Part#	FSP3X3-1Klb	FSP3X3-5Klb	FSP3X3-10Klb	FSP4X4-5Klb	FSP4X4-10Klb
Capacity	1000lb	2000lb	5000lb	5000lb	10000lb
Division	0.2lb	0.5lb	1lb	1lb	2lb
Platform Size	36in X 36in/ 91.4cm X 91.4cm	36in X 36in/ 91.4cm X 91.4cm	36in X 36in/ 91.4cm X 91.4cm	48in X 48in/ 121.9cm X 121.9cm	48in X 48in/ 121.9cm X 121.9cm
Platform Material	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel
Net Weight	159lb / 72kg	159lb / 72kg	159lb / 72kg	265lb / 120kg	265lb / 120kg
Operating Temp.	0 - 40°C / 32 - 104°F	0 - 40°C / 32 - 104°F	0 - 40°C / 32 - 104°F	0 - 40°C / 32 - 104°F	0 - 40°C / 32 - 104°F

*Dimensions and specifications are subject to change without notice.